



EUROTILES HEAVY DUTY TILE ADHESIVE

A high quality thick or thin bed cement-based tile adhesive ideal for fixing ceramic, quarry, slate, marble, homogenous, low porous porcelain and monocoturra tiles in internal and external application for both walls and floors.

Eurotiles Heavy Duty Tile Adhesive can be used to lay tiles onto concrete, cement rendered, block work and rendered brickwork surfaces in both interior and exterior applications.

- Good water resistance
- High bonding strength
- Non-toxic, non-flammable
- Fast hold

Packaging: 25 kg

Storage: 12 months from date of manufacture

HOW TO USE:

Surface Preparation:

- All surfaces must be structurally sound, free from movement, dry, clean, free from oil, grease, wax, dust and other contaminants.
- For painted surfaces; It should be scraped to bare at least 80% of the original substrate
- Newly built concrete must be allowed to cure for 28 days
- Newly rendered surfaces must be allowed to cure for at least 7 days
- For old concrete and rendered surfaces, a strong grade detergent or degreaser must be used to clean the surface, thoroughly washed away the detergent or degreaser with clean water.
- The whole surfaces must be dry for at least 24 hours (no moisture) prior to tiling but must be dampened using sponge or cloth before application.

Mixing and application

- Gradually add 25 kg. of Eurotiles Heavy Duty Tile adhesive to 5 to 6 liters of water into a plastic pail. Mix continuously until a thick creamy consistency is achieved free of lumps (use of electric mixer is highly recommended).

EUROTILES INDUSTRIAL CORPORATION

Unit 201 Prestige Tower, F. Ortigas Jr. Road, Ortigas Center Pasig City
Tel. No.: (632) 635-2310 to 16 Fax No.: (632) 635 2317 www.eurotiles.ph

- Allow the mixture to stand 5-10 minutes, mix again before application.
- Spread the adhesive onto the substrate using a notched trowel.
- Choices of notched trowel depend on the size of the tile, depth knobs, grooves and ridges on the back of the tiles and evenness of the substrate.
- For tiles 300mm x 300mm and up, the adhesive should be placed onto the back of the tiles in addition to the adhesive on the substrate.
- Do not allow the adhesive to skin over prior to tiling.
- During installation, press the tiles onto the tile adhesive first. Then, move it against the notched trowel line while fixing or adjusting tile on its position.

Note: The adhesive coverage must be uniform and cover the entire tile thoroughly. The advised thickness must be approximately half the height of the square notched trowel used. Ensure that there are no voids under the tiles.

Cleaning and Grouting

- Allow the tiling to set for 24 hours before grouting with Eurotiles Superior Tile Grout.
- Wipe off residue on the tile surface with wet foam (clean water). Hands and tools can be cleaned with water.
- Proper tile spacing must be observed. At least 3mm width is needed to allow possible movement of tile due to shrinkage and thermal formation and also to prevent tile cracking and mullet.

TECHNICAL DATA:

Compressive Strength: 28 days = 2000psi

Bonding Strength: 7 days = > 1mpa

28 days = > 1.30mpa

***DISCLAIMER:** Due to different working method, the manufacturer is not liable for any damage and faulty outcome arising from incorrect use of this product. Please follow the instructions mentioned above.*