



EUROTILES

Quick Leveller Thin

Eurotiles Quick Leveller Thin is a self-levelling ready to mix mortar for preparing substrate before laying thin-floor coverings in 3-8 mm thickness applications. It can be used on both old and new floors.

USES

- Interior floors that require smooth and even surfaces
- Permissible substrate: concrete slabs, mortar screed, pre-fabricated elements
- Possible covering materials: vinyl sheeting, tiles, carpet, parquet, rubber, floor paints

ADVANTAGES

- Excellent adhesion
- Self-levelling and self-smoothing
- Quick opening to traffic
- Compatible with traditional floor coverings

TECHNICAL DATA

	Days	MPa	PSI
Bond Strength By Pull-Off Test ASTM C1583	7	1.04	150
	28	1.50	217
Compressive Strength ASTM C109	7	21.47	3113
	28	35.87	5129

Coverage:	2 kg/m ² /mm
Packaging:	25 kg bag
Storage:	Cool, dry place
Shelf life:	12 months from date of production

HOW TO USE

A. Substrate Preparation

1. Substrate must be compliant with building regulations and must be cured for at least 28 days.
2. Surface must be clean and sound, solid, free from dust and other contaminants, without any trace of oil, grease, laitance, curing compound, cracks, plaster, paint and any other products that may affect bonding.
3. Brush off, scrape off, or vacuum off all traces of plaster, paint, laitance and non-bonded adhesive.
4. Substrates with excessive traces of wax, grease or paint must be stripped off.
5. The substrate must be soaked in water for a couple of hours before application of Eurotiles Quick Leveller Thin until no bubbles are present. Remove excess water prior to priming.

B. Priming

Apply Eurotiles Primer Kote onto the substrate. The layer must be dry when pouring on Euroiles Quick Leveller Thin.

C. Product Preparation

Mix one 25 kg bag of Eurotiles Quick Leveller Thin with 4.5 to 5 liters of clean Water using a mechanical stirrer. Mix well until a lump-free, homogeneous consistency is achieved. **NO WATER** should be added once the mortar has been set.

D. Joints

1. Lay a plastic tracking strip or use a machine saw when making joints.
2. If the surface is to be painted or left bare, allow a maximum distance of 8mm for every 25 m² area.
3. Allow a maximum distance of 10 mm for every 50m² in all other cases
4. Pre-existing construction or expansion joints must be re-inspected.

PRECAUTIONS

- Temperature range: 5°C – 35°C
- Do not mix with other cement or hydraulic binders
- Do not add sand and/or admixtures
- Close all windows, doors and other opened areas to avoid draughts and pre-mature drying during the first few hours after application.
- Do not apply on hot substrate or in full sunlight.

Disclaimer: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

MADE IN TAIWAN

EUROTILES INDUSTRIAL CORPORATION

Unit 201, Prestige Tower, F. Ortigas Jr. Road, Ortigas Center, Pasig City

Tel. No.: (632) 635-2310 to 16 Fax No. (632) 635-2317

www.eurotiles.ph