



EUROTILES SKIMCOAT EXCEL 102 is a ready-to-use smooth rendering paste that can be applied on both interior and exterior walls and ceilings in a thickness of 0.3 to 4mm used to level surface defects in concrete or render.

USES

- Lightweight concrete blocks
- Shuttered concrete
- Reinforced concrete
- Precast concrete
- Concrete soffits
- Fiber cement board

Possible covering materials:

- thick plastic coating
- paint
- wallpaper
- fabric
- bonded plastic coverings

ADVANTAGES

- Ready to use
- Easy to apply
- Superb smooth white finish
- Can be used in interior and exterior application
- Can be painted directly, no primer needed

TECHNICAL DATA

	Days	mpa
Bond strength by Pull-off Test ASTM C1583 After 2 coats	28	≥1

Coverage	25 to 30 sqm per pail @ 2 coats
Packaging	20kg pail
Storage	Cool, dry place
Shelf life	12 months (unopened container)

HOW TO USE

A. Substrate Preparation

- The substrate must be clean and sound, free from dust and other particles and without any trace of oil, grease, laitance, paint or curing compound.
- Excess concrete and seams must be struck off.
- Using a sponge or a cloth, dampen the substrate before applying Eurotiles Skimcoat Excel 102.

B. Application

- Apply small quantities of Eurotiles Skimcoat Excel 102 using a stainless steel trowel, filling knife or spatula.
- Regularly wash tools to remove hardened residues. DO NOT return or mix the residues into the bucket.
- Minimum of two coats must be applied for a successful resurfacing. First coat acts as primer to fill up all minor defects on the surface. Two or more coats can be applied depending on desired smoothness of the surface.

- Depending on the atmospheric condition, thickness application and covering materials, allow 15-30 minutes between each coat of Eurotiles Skimcoat Excel 102.
- Pre-covering curing time is 48-72 hours depending on the application thickness, atmospheric condition and covering materials.

PRECAUTIONS

- Do not apply to a wet or damp surface with moisture content.
- Do not apply the product more than 1mm per coat.
- Do not cover with hydraulic binder based mortar.
- Do not return the residues back to the bucket or pail of fresh, unused Eurotiles Skimcoat Excel 102.

DISCLAIMER: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

PRODUCT MADE IN THE PHILIPPINES

EUROTILES INDUSTRIAL CORPORATION

Km 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite
Tel. No.: (8632) 635-2310 to 16 Fax No.: (632) 8635-2317

Web: www.eurotilesconstructionchemicals.com FB: @eurotilesconstchem IG: @eurotilesconstchem YT: Eurotiles Industrial Corporation