



EUROTILES PLASTER PATCH 104 is a rendering mortar with 2 mm to 10 mm thickness used for repairing surface defects on traditional renders or on the concrete panels of walls and/or ceilings.

ADVANTAGES

- With high bonding strength
- Compatible with decorative wall coverings
- Interior and exterior applications
- Easy to use
- Low VOC

TECHNICAL DATA

	days	mpa	psi
Bond strength by Pull-off Test ASTM C1583	7	≥0.8	116
	28	≥1	145
Compressive Strength ASTM C019	7	13.79	2,000
	28	17.23	2,500

Coverage	10sqm per bag at 2mm Thickness
Packaging	25kg bag
Storage	cool, dry place
Shelf life	12 months (unopened bag)

HOW TO USE

A. Substrate Preparation

- The substrate must be clean and sound, free from dust and other particles and without any trace of oil, grease, laitance, paint or curing compound.
- Excess concrete and seams must be cut off.
- Using a sponge or a cloth and dampen the substrate before applying Eurotiles Plaster Patch 104.

B. Product Preparation

- Combine 25kg bag of Eurotiles Plaster Patch with 4 - 4.5L of clean water for overhead application or 5-5.5L of water for vertical walls. Mix thoroughly with a mechanical stirrer or by hand until a homogeneous consistency is achieved.
- Do not add water after mixing.
- Let the mixture stand for several minutes.
- Mix again before application.

C. Application

- Using a stainless steel trowel or rubber float, apply the mortar onto the substrate.
- Apply a continuous force by lightly rubbing in a circular motion with a steel trowel (semi-smooth finish) or with a rubber/wood float (rough finish).
- Let the substrate cure for 7 days depending on the thickness and atmospheric conditions before applying any covering material.

PRECAUTIONS

- Temperature range: 5°C to 35°C
- Protect the finished surface from drying out by lightly moistening during hot conditions by lightly misting the surface.
- Do not apply gypsum-based substrate.
- Do not mix with other hydraulic binders/cement.

DISCLAIMER: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

PRODUCT MADE IN THE PHILIPPINES

EUROTILES INDUSTRIAL CORPORATION

Km. 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite

Tel. No.: (632) 8635-2310 to 16 Fax no: (632) 8635-2317

Web: www.eurotilesconstructionchemicals.com FB: @eurotilesconstchem IG: @eurotilesconstchem YT: Eurotiles Industrial Corporation