



## SUPERIOR TILE GROUT

**EUROTILES SUPERIOR TILE GROUT** A designer's joint tile filler developed to enhance the ceramic tiles' aesthetic value. It is used to fill the gap between laid ceramic tiles. Contains hydrophobic compound that prevents seepage of water under installed ceramic tiles which may eventually darken the tiles. High impact resistance.

### TECHNICAL DATA

<b>Compressive Strength</b>	15 N / mm <sup>2</sup>
<b>Working Temperature</b>	10°C to 38°C (substrate temperature)
<b>Curing time</b>	24 hours
<b>Mixing Ratio</b>	approx. 00 ml for 2kg bag or 300ml/kg

<b>Material basis</b>	White cement with pigments and hydrophobic compound.
<b>Color</b>	10 available colors <small>(White , Beige , Brown , Black , Cream , Ochre , Mint Green , Blue , Gray , Light Brown)</small>
<b>Shelf life</b>	approx. 12 months
<b>Storage</b>	cool, dry place
<b>Packaging</b>	2kg bag

<b>Tile Format</b>	<b>Suggested Gap</b>	<b>2kg bags covers approx.</b>
20x20 to 30x30	4mm - 6mm	4 - 6 m <sup>2</sup>
30x30 cm and UP	6mm-8mm	4 - 6 m <sup>2</sup>

### HOW TO USE

#### GROUTING

1. Pour Eurotiles Superior Tile Grout powder into clean plastic container. Slowly add water, stirring continually until thick paste. Allow to stand for 10minutes, stir again and use within an hour. Do not use salty or brackish water.
2. Apply the grout mixture diagonally across the tile joints, applying enough pressure, and eliminating trapped air. Rub the exposed surface to make even. Let stand for (5) minutes.
3. Wipe excess grout with a damp sponge or clean cloth using the same diagonal strokes until the grout is completely leveled with the tiles.
4. Wring out as much water as possible from the cleaned sponge or cloth and tool the filled joints by lightly running the sponge along the tile grout lines.
5. Smooth the grout with a clean, soft and dry cloth, wiping off any remaining residue.
6. Protect the grouted areas by placing barriers or covering for at least 24 hours before resuming normal activities in the area.

#### PRECAUTIONS

- Do not apply at temperatures above 38°C and under exposure to strong wind and sunlight.
- The open time reduces with absorbent substrates.
- Clean tools with water immediately after use; once the product has cured it can only be removed by mechanical means.

#### SAFETY

Eurotiles Superior Tile Grout contains cement. Cement is irritating to skin. Contact with moisture sets off an alkaline reaction which may cause skin irritation and/or caustic burns to mucous membranes (e.g. eyes). Risk of serious damage to eyes.

Avoid contact with skin and eyes. Wear suitable protective gloves and eye/face protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, take off immediately all contaminated clothing and wash immediately with plenty of water and soap. Keep out of the reach of children. If swallowed, seek medical advice and show container or label. Product is low in chromates

v082824 Eurotiles Superior Tile Grout 1 of 1

### EUROTILES INDUSTRIAL CORPORATION

Km 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite  
Tel. No.: (632) 8635-2310 to 16 Fax No.: (632) 8635-2317

www.eurotilesconstructionchemicals.com FB: @eurotilesconstchem IG: @eurotilesconstchem YT: Eurotiles Industrial Corporation