



Sealer Matte/Gloss is a single component high performance primer engineered from from quality silicone copolymer resins. The product is designed to deliver excellent offers resistance to weathering for both external and internal surface applications, as well as outstanding water repellence to masonry surfaces.

Sealer Matte/Gloss® has the ability to cure at room temperature, even without exposure to extreme heat. It has an anionic property that provides a durable bond which makes it extremely resistant to water. Its advance formulation helps **Sealer Matte/Gloss®** to retain its semi-transparent color on any weather condition, with self-cleaning characteristics that repels water, oil, and other dirt.

APPLICATION

Suitable for use as a sealer, primer and waterproofing topcoat for industrial applications that require quick curing time, excellent weathering resistance and outstanding water repellence. Can be applied to both internal and external external and internal surface applications, masonry projects, etc.

TECHNICAL DATA

Abstract	Acrylate Functional Polymer (W/O/W Multiple Emulsion)
Appearance	Semi-transparent emulsion
Solid content	32~34%
Viscosity	<1,000 cps
PH	7.5~8.5

Test Project	Test Values	Test Modes
Adhesion	25.7 Kg/cm ²	CNS8082
Recoating	Apply Barrier-free	CNS 10756
Water Resistance	5.8% (50 Place in water 7)	

Weathering resistance (Chromatic aberration)	Early	1,000 After hours		2,000After hours	
	94.9%	94.1%		93.5%	
Weathering resistance (Gloss)	Early	1,000After hours		2,000After hours	
	79.3%	Gloss	Gloss retention	Gloss	Gloss retention
		76.9%	97%	65.8%	83%

Water resistance CNS10757 CNS8082	
Appearance	No expansion, Crack, Stripping
Adhesive Strength	16.7 Kgf/cm ²
Acid and alkali resistant adhesive CNS10757 CNS8082	
Adhesive Strength	9.08 (acid), 13.1 (alkali) Kgf/cm ²

HOW TO USE

A. Substrate Preparation

The substrate must be clean and free from any dust, dirt, oils, greases or incompatible sealers that may interfere with adhesion. Do not apply if the surface is contaminated. It is highly recommended to test all substrates prior to application.

B. Directions

For the best results, prepare a clean surface. Sealer Matte or Gloss can be applied using a brush, a roller or an airbrush/spraybrush.

PACKAGING & STORAGE

- Sealer Matte/Gloss comes in a 20 kg packaging (plastic pail).
- The product must be stored in a dry environment to be used within 12 months from the date of manufacture. When using the product, good ventilation is required. Seal tight lid after every use.

Disclaimer: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

MADE IN TAIWAN

EUROTILES INDUSTRIAL CORPORATION

Km 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite
Tel. No.: (632) 8635-2310 to 16 Fax No.: (632) 8635-2317

Web: www.eurotilesconstructionchemicals.com FB: @eurotilesconstchem IG: @eurotilesconstchem YT: Eurotiles Industrial Corporation