



**EUROTILES QUICK PLUG 208** is an ultra-fast-setting hydraulic mortar that stops leaks by hardening within 60-90 seconds while increasing in volume. It offers long-term protection against recurring water leakage on the plugged area.

## USES

- Floor-wall joints
- Sealing injectors and drains
- Underground structures
- Toilets and swimming pools
- Water tanks, reservoirs and gutters

## ADVANTAGES

- Ultra-fast-setting, hardens in 60-90 seconds
- High resistance to pressure
- For interior and exterior use

## TECHNICAL DATA

<b>Setting Time</b>	60 - 90 seconds
<b>Appearance</b>	Gray powder
<b>Particle Size</b>	0 - 0.5mm
<b>Coverage</b>	varies per use
<b>Packaging</b>	20 kg/pail
<b>Storage</b>	cool, dry place
<b>Shelf life</b>	12 months (unopened container)

## HOW TO USE

### A. Substrate Preparation

- The substrate must be clean and sound, free from dust and other loose particles and without any trace of oil.
- Before application, dampen the substrate with clean water for preventive care and sealing.

### B. Product Preparation

- Mix a small quantity of Eurotiles Quick Plug 208 with clean water to obtain a plastic-like consistency

### C. Application

- Apply Eurotiles Quick Plug 208 by hand and press it firmly for several seconds until it hardens.
- High-flow waterways should be sealed in several stages. The cooled area must be kept damp for 15 minutes.

## D. Specific Application

---

- Waterproofing wall to floor joints: Make a regular incision at least 2 cm wide and deep to the area where the leaks appear.
- High pressure leaks: Start filling the areas which are subjected to the lowest pressure, work in stages just before doing the filling on the high pressure area. When doing the final seal, make a ball of mortar and press it firmly.

## PRECAUTIONS

- Temperature range: 5°C- 35°C
- Keep the product surface damp for 15 minutes after application.
- Always wear hand gloves and clean the tools immediately after use.

**DISCLAIMER:** Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

**PRODUCT MADE IN TAIWAN**

### EUROTILES INDUSTRIAL CORPORATION

Km 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite  
Tel. No.: (8632) 635-2310 to 16 Fax No.: (632) 8635-2317

Web: [www.eurotilesconstructionchemicals.com](http://www.eurotilesconstructionchemicals.com) FB: @eurotilesconstchem IG: @eurotilesconstchem YT: Eurotiles Industrial Corporation