



EUROTILES BITU KOTE RUBBER 214 is a water-based rubberized asphalt elastic waterproofing material. It is composed of emulsion and asphalt and various other special functional materials.

ADVANTAGES

- Good adhesive strength even on damp or wet surface.
- Coating have self-adhesive function and automatically mend the fissures on concrete.
- One component and easy to use.
- Low viscosity, high solid content.
- Water-based, environment friendly, non-flammable.
- Superior permeability and adhesive strength, durable waterproofing function.

TECHNICAL DATA

TEST ITEM	TEST METHOD	TEST
Tensile Strength	CNS 3553 (1996) (no. 5 Specimen * V=500mm.min)	5
Elongation		600
Water Resistance (600hrs)	Refer CNC 15666(2013) (Remark) ASTM D2244-11NS 3553 (1996)	
A. Total Color Difference		2
B. Tensile Strength (kgf/cm ²)		4
C. Elongation		10

DRYTIME	1-2 hours
COVERAGE	approx. 18 sq.m @ 2 coats
PACKAGING	18 kg pail
STORAGE	cool and dry place
SHELF LIFE	12 months (unopened container)

HOW TO USE

- Reinforce all cracks, corners and fragile parts before applying Eurotiles BITU KOTE Rubber.
- Open the can to use.
- Apply Eurotiles Bitu Kote Rubber 214 using a brush, roller or convection spray equipment.
- Three layers must be applied on installations.
- Fiber cloth may be inserted between layers to reach a superior effect.

DISCLAIMER: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

PRODUCT MADE IN TAIWAN

EUROTILES INDUSTRIAL CORPORATION

Km 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite
Tel. No.: (632) 8635-2310 to 16 Fax No.: (632) 8635-2317

Web: www.eurotilesconstructionchemicals.com FB: @eurotilesconstchem IG: @eurotilesconstchem YT: Eurotiles Industrial Corporation