



EUROTILES ULTRA KOTE PLUS 224 is a one component flexible acrylic waterproofing paint for interior and exterior use. It is recommended to use on balconies, roofdecks, firewalls and facades.

ADVANTAGES

- Ready to use and easy to apply
- Excellent adhesion to concrete and most substrates
- Superior flexibility, durability and weather resistant
- High water resistance
- Can bridge hairline cracks and block pinholes
- Interior and exterior application

TECHNICAL DATA

Paste Density	1.34 - 1.40	Appearance	Liquid paste
Paste Viscosity	3,000 - 10,000 cP	Shore hardness ASTM D2240	50 - 52
pH	8.00 - 9.00	Coverage	25 to 30 sqm per pail @ 2 Coats (may vary depending on substrate conditions)
Solid Content (by weight)	60 - 70%	Shelf life	6 months (unopened container)
Water Vapor Transmission ASTM D1653	70 - 80 g/m ² /24hr	Packaging	25kg pail
Bond Strength by pull-off adhesion test ASTM C1583	2.50 - 3.00 MPa		

HOW TO USE

A. Surface Preparation

- The substrate must be fully cured, level and structurally stable. It should be clean and free of dust, oil, paint, curing compound and other coatings.

B. Mixing

- Ready to use, mix well prior to use. Can be diluted with water for priming.

C. Application

- Using brush or roller, apply first coat of Eurotiles UltraKote Plus 224 in prepared surface. Allow to dry 1 - 2 hours depending on temperature or weather condition prior to application of second coat.

DISCLAIMER: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

MADE IN THE PHILIPPINES

EUROTILES INDUSTRIAL CORPORATION

Km 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite
Tel. No.: (632) 8635-2310 to 16 Fax No.: (632) 8635-2317

Web: www.eurotilesconstructionchemicals.com FB: @eurotilesconstchem IG: @eurotilesconstchem YT: Eurotiles Industrial Corporation