



EUROTILES PREMIUM BONDING AGENT 118 is a multi-purpose primer consisted mainly of an imported and newly synthesized water-based resin. It shows optimal concrete bonding and superior adhesion on various bases, including tile, glass, PVC and metal surface. Also with its excellent alkaline-acid resistance and waterproof feature, it can also be mixed with polymer clay and concrete sand as the concrete sealer for further adhesion enhancement.

USES

- Sealer for concrete surfaces
- Sealer for reinforced concrete
- Binder for tile, mosaic, marble, PVC surface, metal and aging surface

ADVANTAGES

- Superior adhesion and bonding on broad range of surfaces, including concrete, asbestos and other surfaces.
- Consisted of great elasticity, high penetration, and adhesion characters.
- Its adhesion ability can be greatly enhanced by mixing with concrete sand, forming rough surface after drying.
- Excellent waterproof and environmental characters, with alkaline-acid resistant ability.

TECHNICAL DATA

Practical Coverage	60 to 70 sqm per pail / @ 1 Coat
Dry Time at 25°C and 60% RH	1 - 2 hours *Full cure: 3 - 4 hours
Recoat Time	2 - 4 hours
Application Tool	roller / brush
Packaging	18.5 ± 0.5Kg
Shelf life	24 months (unopened pail)

HOW TO USE

A. Substrate Preparation

- New concrete must cure for a minimum of 30 days before the application.
- Remove all loose and defective paint, oil, fluid, moss or other substances on the surface.
- In severe cases, please wash the surface with water, and make sure the surface is completely dried and clean. All holes or cracks must be properly patched.

B. Primer Applications

- Stir paint thoroughly before use. Intermix containers of same product to ensure color and sheen uniformity.

Surfaces	Usage and Dilution
Interior Wall	Diluted with 3-5 times of water
Exterior wall and rooftop (concrete)	Diluted with 2-3 times of water
Tiles and marbles	DO NOT dilute, please use it directly
Glass, metal and PVC	DO NOT dilute, please use it directly
Use as a concrete sealer	Mixed with concrete sand with (1:1-2)

PRECAUTIONS

- Do not use if rain or heavy dew is expected within 24 hours.
- Avoid applying the product when the temperature is below 50°F (10°C).
- After container is opened, please use the product immediately and prevent long-term storage.
- Product should be store in the cool area, please avoid direct sunlight contact to prevent deterioration.
- Practical coverage is for reference only, which can be differ depending on the brushing surface, flatness and thickness.
- Above dry time is for reference only, longer dry time may be required depending on brushing thickness, higher humidity and cooler temperature condition.

DISCLAIMER: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

PRODUCT MADE IN TAIWAN

EUROILES INDUSTRIAL CORPORATION

Km 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite
Tel. No.: (632) 8635-2310 to 16 Fax No.: (632) 8635-2317

Web: www.eurotilesconstructionchemicals.com FB: [@eurotilesconstchem](https://www.facebook.com/eurotilesconstchem) IG: [@eurotilesconstchem](https://www.instagram.com/eurotilesconstchem) YT: Eurotiles Industrial Corporation