



Eurotiles Quick Fix Plus 120 is a flowable repair mortar for roads and floors. It is easy to apply and has a high mechanical strength. It is used for repairs of scaling/local flaking concrete roads and industrial flooring with thickness from 2mm-10mm.

ADVANTAGES

- Easy to apply
- High mechanical strength
- Self-leveling and Self Compact
- Cost Saving

TECHNICAL DATA

	Days	mpa	psi
Compressive Strength ASTM C109	7	11.72	1,700
	28	31	4,500
Bonding Strength	7	1.20	
	28	1.40	

Packaging	25kg bag
Storage	cool, dry place
Shelf life	12 months (unopened bag)
Coverage	1sqm @ 15mm thickness per bag

HOW TO USE

1. Mix Eurotiles Quick Fix Plus 120 with 4.50 L of clean water using a machine stirrer, mix thoroughly until it is evenly distributed and lump free.
2. Make sure the substrate is sound and free of dust.
3. Carefully check the substrate for cracks
4. It is recommended to do sawing in marking the boundaries of the area to be repaired.
5. Leave 1cm thickness and clean ridges when removing damages materials. Get rid of loose particles and all traces of oil and grease.
6. Rinse thoroughly after removing the dust
7. Soak in water for several hours after cleaning the area, eliminate excess water.
8. Gradually pour the mixture onto the substrate prepared in accordance with instructions mentioned above.
9. Once the mixture has been cast a stainless roller float or screed board should be used to assist the product for leveling.
10. Lay a plastic tracking strip or use a machine saw when making joints
11. If the surface is to be painted or left bare, allow a maximum distance of 8mm for every 25m² area.
12. Allow a maximum distance of 10mm for every 50m² in all other cases
13. Pre-existing construction or expansion joints must be re-inspected.

PRECAUTIONS

- Precautions:temperature range: 5°C- 35°C
- Do not mix with other cement or hydraulic binders
- Do not add sand and/or admixtures
- Do not apply on hot substrate or in full sunlight

DISCLAIMER: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

PRODUCT MADE IN THE PHILIPPINES

EUROILES INDUSTRIAL CORPORATION

Km 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite
Tel. No.: (632) 8635-2310 to 16 Fax No.: (632) 8635-2317

Web: www.euroilesconstructionchemicals.com FB: [@euroilesconstchem](https://www.facebook.com/euroilesconstchem) IG: [@euroilesconstchem](https://www.instagram.com/euroilesconstchem) YT: Eurotiles Industrial Corporation