



**EUROTILES PLASTER PATCH 104** is a rendering mortar with 2 mm to 10 mm thickness used for repairing surface defects on traditional renders or on the concrete panels of walls and/or ceilings.

## ADVANTAGES

- With high bonding strength
- Compatible with decorative wall coverings
- Interior and exterior applications
- Easy to use
- Low VOC

## TECHNICAL DATA

	days	mpa	psi
<b>Bond strength by Pull-off Test</b> ASTM C1583	7	≥0.8	116
	28	≥1	145
<b>Compressive Strength</b> ASTM C019	7	13.79	2,000
	28	17.23	2,500

<b>Coverage</b>	1.3kg / m <sup>2</sup> / mm
<b>Packaging</b>	25kg bag
<b>Storage</b>	cool, dry place
<b>Shelf life</b>	12 months (unopened bag)

## HOW TO USE

### A. Substrate Preparation

- The substrate must be clean and sound, free from dust and other particles and without any trace of oil, grease, laitance, paint or curing compound.
- Excess concrete and seams must be cut off.
- Using a sponge or a cloth and dampen the substrate before applying Eurotiles Plaster Patch 104.

### B. Product Preparation

- Combine 25kg bag of Eurotiles Plaster Patch with 4 - 4.5L of clean water for overhead application or 5-5.5L of water for vertical walls. Mix thoroughly with a mechanical stirrer or by hand until a homogeneous consistency is achieved.
- Do not add water after mixing.
- Let the mixture stand for several minutes.
- Mix again before application.

### C. Application

- Using a stainless steel trowel or rubber float, apply the mortar onto the substrate.
- Apply a continuous force by lightly rubbing in a circular motion with a steel trowel (semi-smooth finish) or with a rubber/wood float (rough finish).
- Let the substrate cure for 7 days depending on the thickness and atmospheric conditions before applying any covering material.

## ***PRECAUTIONS***

- Temperature range: 5°C to 35°C
- Protect the finished surface from drying out by lightly moistening during hot conditions by lightly misting the surface.
- Do not apply gypsum-based substrate.
- Do not mix with other hydraulic binders/cement.

**DISCLAIMER:** Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

**PRODUCT MADE IN THE PHILIPPINES**

## **EUROTILES INDUSTRIAL CORPORATION**

Km. 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite

Tel. No.: (632) 8635-2310 to 16 Fax no: (632) 8635-2317

Web: [www.eurotilesconstructionchemicals.com](http://www.eurotilesconstructionchemicals.com) FB: @eurotilesconstchem IG: @eurotilesconstchem YT: Eurotiles Industrial Corporation