



EUROTILES CLEAR KOTE 222 is a non-yellowing transparent waterproofing paint is latex-based polyacrylic emulsion. This low-odor, water-based formula provides non-pigmented barrier to water on various types of surfaces that requires waterproofing.

ADVANTAGES

- Environmental water-based material.
- Transparent coating film with non-yellowing feature.
- Resistant in all weather conditions
- Durable against scrubbing.

USES

- Stone, tile, wood, metal and other texture of material that requires top-coating protection and waterproofing.

TECHNICAL DATA

Dry Time	Touch Dry: 3-4 hours @ 25°C & 60% RH Full Cure: 6-8 Hours
Recoat Time	3 - 4 hours
Application Tool	Roller, brush, sprayer
Viscosity @ 25°C	13,000 - 14,000 mPa
Coverage	59-66m ² /5 gal
Packaging	18.5+0.5Kg pail
Storage	cool, dry place
Shelf life	24 months (unopened container)

HOW TO USE

A. Surface Preparation

- Remove all loose and defective paint, oil, fluid, moss or other debris and impurities on the surface.
- In severe cases, please wash the surface with water, making sure the surface is complete dry and clean.

B. Top Coat Application

- Stir paint thoroughly before use. Intermix containers of same product to ensure color and sheen uniformity.
- Mixing with water is not recommended. However if required, please dilute with no more than 10% of water.
- Minimum of two coats are required. Third coat is strongly recommended for better result.
- Recoat time is about 3-4 hours.

PRECAUTIONS

- Do not use if rain or heavy dew is expected within 24 hours.
- Avoid applying the product when the temperature is below 50°F (10°C).
- Once container is opened, please use the product immediately. Avoid long-term storage.
- Product should be stored in a cool area. Please avoid exposure to direct sunlight to prevent deterioration.
- Practical coverage is for reference only, which can differ depending on the brushing surface, flatness and thickness.
- Above dry time is for reference only, longer dry time may be required depending on the brushing thickness, higher humidity and cooler temperature condition.

DISCLAIMER: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

PRODUCT MADE IN TAIWAN

EUROTILES INDUSTRIAL CORPORATION

Km 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite
Tel. No.: (632) 8635-2310 to 16 Fax No.: (632) 8635-2317

Web: www.eurotilesconstructionchemicals.com FB: @eurotilesconstchem IG: @eurotilesconstchem YT: Eurotiles Industrial Corporation