



SkimCoat Eco

EUROTILES SKIMCOAT ECO 100 is a smooth rendering liquid to be mixed with cement at thickness of 0.3 to 4mm for use to eliminate grooves, seams and rock pockets in concrete surface for a seamless smooth finish.

USES

- Interior and exterior walls and ceilings from 0.4 to 4mm thickness
- Reinforced concrete
- Pre-cast concrete panels
- Traditional rendering mortars
- Lightweight concrete or lightweight block
- Fiber cement board

ADVANTAGES

- Seamlessly smooth finish
- High bonding strength
- Can be painted directly, no primer needed
- Low VOC

TECHNICAL DATA

	days	mpa	psi
Bond strength by Pull-off Test ASTM C1583 1mm thickness	7	0.80	116
	28	≥1.0	145
Compressive Strength ASTM C109	7	10.34	1,500
	28	15.86	2,300

Coverage	0.6 to 0.8 kg / m ² / 2 coats
Packaging	20kg pail
Storage	Cool, dry place
Shelf life	12 months (unopened container)

HOW TO USE

A. Substrate Preparation

- The substrate must be clean and sound, free from dust and other particles and without any trace of oil, grease, laitance, paint or curing compound.
- Excess concrete and seams must be struck off.
- Using a sponge or a cloth, dampen the substrate before applying Eurotiles Skimcoat Eco 100.

B. Product Preparation

- Mix 1 part of Eurotiles Skimcoat Eco 100 with 1 part cement (1:1) until a homogeneous, lump free consistency is achieved. **Do not add water.**

C. Application

- Using a stainless steel filling knife or trowel, apply Eurotiles Skimcoat Eco 100 onto the substrate.
- Apply a minimum of two coats.
- Depending on the thickness and the atmospheric condition, allow 15-30 minutes between each coat of Eurotiles Skimcoat Eco 100.
- Allow a minimum of 3-7 days for curing depending on the thickness of the coat and the atmospheric conditions.

PRECAUTIONS

- Temperature range: 5°C to 35°C
- Immediately clean tools after application with water before product dries,
- Protect the finished surface from drying out by lightly moistening during hot conditions.
- Do not cover with hydraulic binder based mortar.
- Do not immerse the product.

DISCLAIMER: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

PRODUCT MADE IN THE PHILIPPINES

EUROTILES INDUSTRIAL CORPORATION

Km 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite
Tel. No.: (632) 8635-2310 to 16 Fax No.: (632) 8635-2317

Web: www.eurotilesconstructionchemicals.com FB: @eurotilesconstchem IG: @eurotilesconstchem YT: Eurotiles Industrial Corporation