



Skim Coat Eco

Eurotiles Skimcoat ECO is a smooth skin rendering liquid to be mixed with cement at thickness of 0.3 to 4mm for use to eliminate grooves, seams and rock pockets in concrete surface for a seamless smooth finish.

USES

- *Eurotiles Skimcoat ECO* can be applied to both interior and exterior walls and ceilings from 0.3 to 4 mm thickness.
- Reinforced concrete
- Pre-cast concrete panels
- Traditional rendering mortars
- Lightweight concrete or lightweight block
- Fiber cement board

ADVANTAGES

- Seamlessly smooth finish
- High bonding strength
- For interior and exterior use
- Can be painted directly , no primer needed

TECHNICAL DATA

	Days	MPa	PSI
Bond Strength by Pull-Off Test ASTM C1583 1 mm thickness	7	1.23	178
	28	1.31	190
Compressive Strength ASTM C109	7	11	1595
	28	20	2900

Coverage -	0.6-0.8 kg/m ² / 2 coats
Packaging -	20 kg pail
Storage -	Cool, dry place
Shelf life -	12 months (unopened container)

HOW TO USE

A. Substrate Preparation

1. The substrate must be clean and sound, free from dust and other particles and without any trace of oil, grease, laitance, paint or curing compound.
2. Excess concrete and seas must be struck off.
3. Using a sponge or a cloth, dampen the substrate before applying Eurotiles Skimcoat ECO.

B. Product Preparation

Mix 1 part of Eurotiles Skimcoat ECO with 1 part cement until a homogenous, lump free consistency is achieved. **DO NOT ADD WATER.**

C. Application

1. Using a stainless steel filling knife or trowel, apply Eurotiles Skimcot ECO onto the substrate.
2. Apply a minimum of 2 coats.
3. Depending on the thickness and the atmospheric conditions, allow 15-30 minutes between each coat of Eurotiles Skimcoat ECO.
4. Allow a minimum of 7 days for curing depending on the thickness of the coat and the atmospheric conditions.

PRECAUTIONS

- Temperature range: 5°C – 35°C
- Immediately clean tools after application with water before product dries
- Protect the finished surface from drying out by lightly moisting during hot conditions
- Do not cover with hydraulic binder based mortar
- Do not immerse the product

Disclaimer: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

MADE IN THE PHILIPPINES

EUROTILES INDUSTRIAL CORPORATION

Unit 201, Prestige Tower, F. Ortigas Jr. Road, Ortigas Center, Pasig City

Tel. No.: (632) 635-2310 to 16 Fax No. (632) 635-2317

www.eurotiles.ph