



EUROTILES SOLAR KOTE GLOSS 220 is derived from the spaceship cabin's anti-radiant and waterproofing technology. Solar Kote Gloss 220 consists of superior quality raw materials specially formulated to provide extreme heat-resistant ability. It provides a solution to the humidity problem of iron sheet surfaces, gives comfortable indoor environment, and also increases the energy efficiency of the building.

ADVANTAGES

- Great anti-ultraviolet, anti-acid and anti-alkaline characteristics with excellent weather durability.
- Capable of isolating radiant heat and decreasing 6°C of indoor temperature when the outdoor temperature is over 36°C. Greater effect can be observed with higher outdoor temperature.
- Prevents mold, bacteria and moss from growing.
- Can be applied directly on the metal surface.
- Specialized imported glass bubbles sufficiently reduces radiant heat.
- Low VOC

USES

- Concrete-based surfaces, metal surfaces, wooden houses, asbestos tiles, storage, and other surfaces that require anti-heat, waterproofing and anti-corrosion characteristics.

TECHNICAL DATA

Dry Time	Touch Dry: 3-4 hours @ 25°C & 60% RH Full Cure: 6-8 Hours
Recoat Time	6 - 8 hours
Application Tool	Roller, trowel, brush, sprayer
Viscosity @ 25 °C	13,000 - 14,000 mpa
Coverage	59-60m ² /5 gal
Packaging	21+0.5Kg pail
Storage	cool, dry place
Shelf life	24 months (unopened container)

HOW TO USE

A. Surface Preparation and Recommended Primer

- New concrete must be cured for a minimum of 30 days before application.
- Remove all loose and defective paint, oil, fluid, moss or other substances on the surface.
- In severe cases, please wash the surface with water, making sure that the surface is completely dry and clean. All holes or cracks must be properly patched.
- Primer: Minimum of one coat is required. Primer is not required when applying on a metal surface.

B .Top Coat Application

- Stir paint thoroughly before use. Intermix containers of same product to ensure color and sheen uniformity.
- Mixing with water is not recommended. However if required, please dilute with no more than 10% water.
- Minimum of two coats are required. Recoat time is about 6 - 8 hours.

PRECAUTIONS

- Do not use if rain or heavy dew is expected within 24 hours.
- Avoid applying the product when the temperature is below 50°F (10°C).
- Once container is opened, please use the product immediately. Avoid long-term storage.
- Product should be stored in a cool area. Please avoid exposure to direct sunlight to prevent deterioration.
- Practical coverage is for reference only, which can differ depending on the brushing surface, flatness and thickness.
- Above dry time is for reference only, longer dry time may be required depending on the brushing thickness, higher humidity and cooler temperature condition.

DISCLAIMER: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

PRODUCT MADE IN TAIWAN

EUROTILES INDUSTRIAL CORPORATION

Km 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite
Tel. No.: (632) 8635-2310 to 16 Fax No.: (632) 8635-2317

Web: www.eurotilesconstructionchemicals.com FB: @eurotilesconstchem IG: @eurotilesconstchem YT: Eurotiles Industrial Corporation