



EUROTILES QUICK PLUG 208 is an ultra-fast-setting hydraulic mortar that stops leaks by hardening within 60-90 seconds while increasing in volume. It offers long-term protection against recurring water leakage on the plugged area.

USES

- Floor-wall joints
- Sealing injectors and drains
- Underground structures
- Toilets and swimming pools
- Water tanks, reservoirs and gutters

ADVANTAGES

- Ultra-fast-setting, hardens in 60-90 seconds
- High resistance to pressure
- For interior and exterior use

TECHNICAL DATA

| | |
|----------------------|--------------------------------|
| Setting Time | 60 - 90 seconds |
| Appearance | Gray powder |
| Particle Size | 0 - 0.5mm |
| Coverage | varies per use |
| Packaging | 20 kg/pail |
| Storage | cool, dry place |
| Shelf life | 12 months (unopened container) |

HOW TO USE

A. Substrate Preparation

- The substrate must be clean and sound, free from dust and other loose particles and without any trace of oil.
- Before application, dampen the substrate with clean water for preventive care and sealing.

B. Product Preparation

- Mix a small quantity of Eurotiles Quick Plug 208 with clean water to obtain a plastic-like consistency

C. Application

- Apply Eurotiles Quick Plug 208 by hand and press it firmly for several seconds until it hardens.
- High-flow waterways should be sealed in several stages. The cooled area must be kept damp for 15 minutes.

D. Specific Application

- Waterproofing wall to floor joints: Make a regular incision at least 2cm wide and deep to the area where the leaks appear.
- High pressure leaks: Start filling the areas which are subjected to the lowest pressure, work in stages just before doing the filling on the high pressure area. When doing the final seal, make a ball of mortar and press it firmly.

PRECAUTIONS

- Temperature range: 5°C- 35°C
- Keep the product surface damp for 15 minutes after application.
- Always wear hand gloves and clean the tools immediately after use.

DISCLAIMER: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

PRODUCT MADE IN THE PHILIPPINES

EUROTILES INDUSTRIAL CORPORATION

Km 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite
Tel. No.: (632) 8635-2310 to 16 Fax No.: (632) 8635-2317

Web: www.eurotilesconstructionchemicals.com FB: @eurotilesconstchem IG: @eurotilesconstchem YT: Eurotiles Industrial Corporation