



EUROTILES SKIMCOAT SUPERFINE is an innovative thin plastering mortar that covers pinholes and other finishing imperfections of concrete walls, columns, beams and ceilings. It can be applied on interior walls and ceilings, precast concrete panels and fiber cement boards.

ADVANTAGES

- Easy to apply
- Excellent workability
- Non-cracking
- Superb smooth surface finish
- Minimal porosity
- Capable to regulate environmental humidity
- Strength of adhesion is above the industry standard

TECHNICAL DATA

| | |
|--|---------------------------|
| Bond strength by Pull-off Test ASTM C1583 1mm thickness | 28 days = ≥ 0.70 mpa |
| Compressive Strength ASTM C109 | $\geq 1,200$ @ 28 days |

| | |
|-----------------------|--|
| Material basis | : White cement, additives and limestone powder |
| Color | : White |
| Coverage | : 17 to 18 / m ² / @ 2 coats |
| Mixing Ratio | : approx. 8 Liters/20 kg bag |
| Thickness | : 0.5 to 3mm |
| Working Temp. | : 10°C to 38°C (substrate temperature) |
| Pot life | : 3 to 4 hours |
| Dry touch | : approx. 30 minutes to 1 hour |
| Curing Time | : 12-24 hours |
| Packaging | : 20kg |
| Storage | : Cool, dry place |
| Shelf life | : 12 months (unopened bag) |

HOW TO USE

A. Substrate Preparation

- Make sure the surface is clean and sound, free from dirt, dust and oil.
- For best result, allow the plastered wall to stand for 7 days before application of Eurotiles Skimcoat Superfine to avoid future cracking.
- Tools needed: Trowel, mixer, plastic bucket or pail, sandpaper

B. Application

- Pour 8 liters of clean water into a plastic pail. Gradually add 20kg of Eurotiles Skimcoat Superfine into the water.
- Mix Eurotiles Skimcoat Superfine for 2 to 3 minutes until the compound is evenly distributed and lump free. The use of electric mixer is highly recommendable.
- Let the mixture stand for 15 minutes and mix again briefly before use.
- Using plain trowel or putty knife, apply the mixture with pressure at 45 degree angle. Let it dry for 30 minutes before applying the second coat.

PRECAUTIONS

- Store at room with cool, dry temperature.
- Keep off the ground.
- Always wear dust mask and gloves when handling product.
- Clean tools immediately after use.
- Product that has been cured can only be removed by mechanical means

DISCLAIMER: Due to different working methods, the manufacturer is not liable for any damages and faulty outcomes arising from incorrect use of this product. Please follow the instructions mentioned above.

PRODUCT MADE IN THE PHILIPPINES

EUROTILES INDUSTRIAL CORPORATION

Km 39 Emilio Aguinaldo Highway, Biga 2, Silang, Cavite
Tel. No.: (8632) 635-2310 to 16 Fax No.: (632) 8635-2317

Web: www.eurotilesconstructionchemicals.com FB: @eurotilesconstchem IG: @eurotilesconstchem YT: Eurotiles Industrial Corporation